



**CRITICAL DIMENSIONS WHEN ORDERING YOUR RIDGE ROOFLIGHT.**

WIDTH DIMENSION & EITHER OF THE LENGTH DIMENSIONS AS ILLUSTRATED ABOVE DEPENDING ON YOUR ROOF DESIGN (FLAT ROOF OR PITCHED ROOF) ARE REQUIRED IN ORDER FOR DUPLUS TO PROCEED.  
 AN OVERALL EXTERNAL KERB TOLERANCE OF ±10mm CAN BE ACCOMMODATED.  
 IF KERB DIMENSIONS ARE OUTSIDE THE SPECIFIED TOLERANCE THE SKYLIGHT FRAME MAY NOT FIT OVER THE KERB AS DESIGNED.  
 STRUCTURAL KERB THICKNESS:  
 75mm MIN KERB THICKNESS IS CRUCIAL TO ENSURE THE ROOFLIGHT IS SUITABLY SUPPORTED.

Rev	Date	Description	Rev By
A		FIRST ISSUE	

THIS DRAWING REMAINS THE COPYRIGHT OF DUPLUS ARCHITECTURAL SYSTEMS LTD. AND MUST NOT BE REPRODUCED WITHOUT PRIOR AUTHORIZATION.

370 Melton Road, Leicester LE4 7SL. Tel: 0116 2610710 Fax: 0116 2610539

DUPLUS

Scale: NTS  
Drawn:

Contact: SB ROOFLIGHTS  
Title: RIDGELIGHT KERB / UPSTAND DETAILS

Job No:  
Prog No: SB018

1/21